Product name:
L-Bead

Short product description
L-Bead comes on a roll and performs like conventional L-Bead. This product requires a very light fill coat to finish. Produced for drywall thickness of 3/8", 1/2" standard, 5/8", and 3/4". Ideal for window returns, sky lights and wall edges.

Product description
- Comes on a roll and performs like conventional L-Bead.
- Produced for drywall thickness of 3/8", 1/2" standard, 5/8", and 3/4".
- Installs using standard compounds. No special tools or fasteners needed. No nail pops.
- Second coat of compound can be applied immediately – very light skim-coat to finish.

Applications
- Window returns
- Sky lights
- Wall edges

Specifications
- 2-1/4" x 100' roll size.
- Color Code BROWN
- Item# LB-100
- 12rls per case. 37lbs. per case. 24 cases per pallet.

Application Instructions

Cut Strait-Flex L-bead to desired length. Fold L-bead in half at the crease with print side facing each other. Apply all purpose compound to corner. Using a 4" or 5" taping knife apply a liberal coat of compound evenly on the corner. Press-bead into wet compound. Adjust if necessary to create a straight line. Wipe down tight with taping knife. Immediately apply a light skim coat of compound over surface and wipe down tight and smooth. Let dry completely over several hours then apply 2nd skim coat, let dry and sand smooth.